

**Swing-out rotor, 4-place,  
for ASTM tubes + 50 ml Babcock bottles**



∠ 90°

$n = 2,000 \text{ min}^{-1}$   
max. RCF 984

**Cat. No.** (without carriers) **4474**

**Swing-out rotor, 6-place,  
for chrome bath tubes**



∠ 90°

$n = 2,000 \text{ min}^{-1}$   
max. RCF 917

**Cat. No.** **4619**<sup>34)</sup>

capacity in ml	50	100	100	100	50
∅ x L in mm	45x130	58x161	44x168	37x200	36.5x185
<b>Cat. No.</b>	-	<b>0528</b>	-	<b>0531</b>	-
carrier Cat. No. <b>4275</b>					
<b>rotor</b> Cat. No. <b>4474</b>					
<b>Cat. No.</b>	<b>4278-A</b>	<b>0771</b>	<b>4277</b>	<b>4276</b>	<b>0703</b>
boring ∅ x L in mm	-				
tubes per rotor	4				
max. RCF	984		961		912
radius in mm	220		215		204
run-up in sec	17				
run-down in sec, braked	20				
temperature in °C <sup>1)</sup>	-8				

capacity in ml	30
∅ x L in mm	24x151
<b>Cat. No.</b>	<b>0529/0508</b> <sup>6)</sup>
<b>rotor</b> Cat. No. <b>4619</b> <sup>34)</sup>	
<b>Cat. No.</b>	-
boring ∅ x L in mm	-
tubes per rotor	6
max. RCF	917
radius in mm	205
run-up in sec	17
run-down in sec, braked	21
temperature in °C <sup>1)</sup>	-11

<sup>1)</sup> Lowest attainable temperature in precooled refrigerated centrifuges at max. speed. Lower temperatures can be attained by reducing the speed.

<sup>6)</sup> A rubber stopper for closing the tube is available under Cat. No. 0535.

The tube may not be centrifuged with the stopper. The stopper only serves to close the tube for agitating or mixing.

<sup>34)</sup> In the heatable models 5660-50, 5660-51, 5660-70, 5670-50 and 5675-50, rotor 4619 may only be used up to a maximum of +40 °C.