




























Angle rotor, 4-place	Angle rotor, 30-place	Angle rotor, 6-place, for PCR strips
		
∠ 25°	∠ 45°	∠ 45°
n = 9,500 min <sup>-1</sup> max. RCF 12,007	n = 15,000 min <sup>-1</sup> max. RCF 24,400	n = 14,000 min <sup>-1</sup> max. RCF 18,845
<b>Cat. No. 4795</b>	<b>Cat. No. 4790-A</b> with bio-containment <sup>6)</sup> , phenol-resistant	lid (optional) Cat. No. 1162 <b>Cat. No. (without lid) 4760</b>

capacity in ml	15	25	94	10	30	50	85	94	250
∅ x L in mm	17x100	24x100	38x102	16x80	26x95	29x107	38x106	38x102	61x122
<b>Cat. No.</b>	<b>0518<sup>2)</sup></b>	<b>0519<sup>2)</sup></b>	<b>0549</b>	-	<b>0545</b>	<b>0546</b>	<b>0547</b>	<b>0538<sup>13)</sup></b>	<b>5127<sup>28)</sup></b>
 <b>rotor</b> Cat. No. 4795									
<b>Cat. No.</b>	<b>5646</b>	<b>5642</b>	<b>5644</b>	<b>5641</b>	<b>5642</b>	<b>5643</b>	<b>5644</b>	-	-
boring ∅ x L in mm	17.6x83	26x80	38.6x88	16.6x70	26x80	29x90	38.6x88	38.6x88	61.5x109
tubes per rotor	28	12	4	32	12	4	4	4	4
max. RCF <sup>2)</sup>	11,301	10,897	10,292	11,402	10,897	10,090	10,292	10,292	12,007
radius in mm	112	108	102	113	108	100	102	102	119
run-up in sec	45								
run-down in sec, braked	55								
temperature in °C <sup>1)</sup>	+2								

capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	0.5
∅ x L in mm	6x18	6x45	8x30	8x45	11x38		10.7x36
<b>Cat. No.</b>	-				<b>2078</b>	<b>0536</b>	<b>Pediatric</b>
lid with bio-containment <sup>6)</sup> incl.							
 <b>rotor</b> Cat. No. 4790-A							
<b>Cat. No.</b>	<b>2024</b>	<b>2023</b>	<b>2031<sup>7)</sup></b>	-	<b>0788</b>		
boring ∅ x L in mm	6x40	8x40	10.2x19	11.2x40.9	11.2x40.9	11.2x40.9	
tubes per rotor	30						15
max. RCF <sup>2)</sup>	24,400						23,394
radius in mm	97						93
run-up in sec	19						
run-down in sec, braked	24						
temperature in °C <sup>1)</sup>	+4						

capacity in ml	0.2	0.2
∅ x L in mm	6x18	-
<b>Cat. No.</b>	-	<b>PCR strips</b>
 <b>rotor</b> Cat. No. 4760		
<b>Cat. No.</b>	-	
boring ∅ x L in mm	6.5x15.5	
tubes per rotor	48	6x8
max. RCF <sup>2)</sup>	18,845	
radius in mm	86	
run-up in sec	15	
run-down in sec, braked	15	
temperature in °C <sup>1)</sup>	+1	

<sup>7)</sup> For centrifugation at high speeds, we recommend to use form-fitting, phenol-resistant adapters 2031.

<sup>13)</sup> The screw cap for tube No. 0538 is available with Cat. No. 0539. Dimensions with cap 38x110 mm.

<sup>28)</sup> At temperatures of over +40 °C and/or when not filled to capacity, bottles may warp during centrifugation.