

Angle rotor, 12-place


Angle rotor, 24-place



∠ 45°

n = 15,000 min⁻¹
max. RCF 16,602










Cat. No. 1612














∠ 40°

n = 15,000 min⁻¹
max. RCF 21,382

Cat. No. 1420-B

capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0
∅ x L in mm	6x18	6x45	8x30	8x45	11 x38	
Cat. No.	-	-	-	-	2078	0536
 lid incl. rotor Cat. No. 1612						
						
Cat. No.	2024	2023	2031⁷⁾	-		
boring ∅ x L in mm	6x40	8x40	10.2x19	11.4x39		
tubes per rotor	12					
max. RCF ²⁾	16,602					
radius in mm	66					
run-up in sec	25					
run-down in sec, braked	23					
temperature in °C ¹⁾	-10					

capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	0.5
∅ x L in mm	6x18	6x45	8x30	8x45	11 x38		10.7 x36
Cat. No.	-	-	-	-	2078	0536	Pediatric
 lid incl. rotor Cat. No. 1420-B							
							
Cat. No.	2024	2023	2031⁷⁾	-			0788²⁰⁾
boring ∅ x L in mm	6x40	8x40	10.2x19	11.2x42.6	11.2x39		
tubes per rotor	24						12
max. RCF ²⁾	21,382						20,376
radius in mm	85						81
run-up in sec	25						
run-down in sec, braked	24						
temperature in °C ¹⁾	-4						

Optional for rotor 1420-B:



lid **Cat. No. 2425**
with bio-containment⁵⁾,
autoclavable



lid **Cat. No. 2423**
with bio-containment⁵⁾,
autoclavable, phenol-resistant

⁷⁾ For centrifugation at high speeds, we recommend to use form-fitting, phenol-resistant adapters 2031.
²⁰⁾ Packed in units of 15 pieces.