

Swing-out rotor, 6-place


Swing-out rotor, 8-place



∠ 90°

n = 4,000 min⁻¹
max. RCF 2,701





Cat. No. (with carriers) **1619**
































∠ 90°

n = 4,000 min⁻¹
max. RCF 2,415

Cat. No. (without carriers) **1611**

capacity in ml	15	50
∅ x L in mm	17x120	29x115
Cat. No.	0509	0513
 rotor Cat. No. 1619		
		
Cat. No.	1462-A	-
boring ∅ x L in mm	17x84	30x87.5
tubes per rotor	6	
max. RCF ²⁾	2,701	
radius in mm	151	
run-up in sec	20	
run-down in sec, braked	22	
temperature in °C ¹⁾	-15	

capacity in ml	5	6	7	10	15	2.6–3.4	2.7–3	4–5.5	4.5–5	7.5–8.5	1.6–5	4–7	4–7	8.5–10	
∅ x L in mm	12x75	12x82	12x100	17x70	13x100	17x100	13x65	11x66	15x75	11x92	15x92	13x75	13x100	16x75	16x100
Cat. No.	0553²⁾	0501²⁾	0578²⁾	2079	-	0518²⁾	blood collection / urine tubes								
 rotor Cat. No. 1611															
															
Cat. No.	1131-A	1643	1132-A	1643	1644	1131-A	1132-A	1643	1644	1131-A	1643	1132-A	1644		
boring ∅ x L in mm	13x53	13.2x81	17.5x53	13.2x81	17.5x81	13x53	17.5x53	13.2x81	17.5x81	13x53	13.2x81	17.5x53	17.5x81		
tubes per rotor	8														
max. RCF ²⁾	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	1,914	2,415	
radius in mm	107	135	107	135	107	135	107	135	107	135	107	135	107	135	
run-up in sec	20														
run-down in sec, braked	20														
temperature in °C ¹⁾	-16														

¹⁾ Lowest attainable temperature in precooled refrigerated centrifuges at max. speed. Lower temperatures can be attained by reducing the speed.

²⁾ Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers. The max. RCF for glass tubes annotated with footnote ²⁾ is 4,000.